

870 Order Status Report

Functional Group=RS

Purpose: This Draft Standard for Trial Use contains the format and establishes the data contents of the Order Status Report Transaction Set (870) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to report on the current status of a requirement forecast, an entire purchase order, selected line items on a purchase order, selected products/services on a purchase order, or purchase orders for a specific customer in their entirety or on a selection basis. The transaction set can also be used to report on the current status of single or multiple requisitions. The report format allows for the inclusion of "reasons" relative to the status. This transaction set may also be used to update the supplier's scheduled shipment or delivery dates. This transaction set can result from either an inquiry or a prearranged schedule agreed to by the trading partners.

Federal Note:

1. Organizations use this transaction set to respond to a Notice of Availability (NOA) providing shipment instructions for material reported available for shipment.
2. Use a single occurrence of this transaction set to transmit single or multiple NOA replies to one or more organizations.
3. DoD logistics users should refer to the Defense Logistics Management System (DLMS) Supplement to the Federal Implementation Convention (IC) available at URL: <http://www.dla.mil/j-6/dlms>. The DLMS Supplement provides specific business rules, conditions, and authorized codes necessary for appropriate use of this IC within the DLMS.

DLMS Note:

1. Country Representatives/Freight Forwarders (CRs/FFs) use this transaction set to respond to a Foreign Military Sales (FMS) Notice of Availability (NOA) providing shipment instructions for material reported available for shipment.
2. Users operating under the Defense Logistics Management system (DLMS) must reference the Unit of Issue and Purchase Unit Conversion Table and the Accounting Classification Appendix which can be found on the Defense Logistics Management Standards web site at <http://www.dla.mil/j-6/dlms>.
3. This DLMS Supplement contains:
 - a. Data associated with a DLMS enhancement which may not be received or understood by the recipient's automated processing system. DLMS procedures may not have been developed. Components must coordinate requirements and business rules with Defense Logistics Management Standards prior to use.
 - b. Data associated with an Approved Change which may not have an established implementation date. This data may not be received or understood by the recipient's automated processing system. Components must coordinate implementation with Defense Logistics Management Standards prior to use.
 - c. Defense Logistics Standard System (DLSS) data which must be retained in the DLMS for a transition period to support transaction conversion in a mixed DLSS/DLMS environment. This data will be streamlined out once full DLMS implementation is reached. Components may coordinate with Defense Logistics Management Standards for early termination (or retention) of specific data requirements for users operating in a full DLMS environment.
 - d. Data elements which have an expanded files size above existing DLSS capability which may not be supported by the recipient's automated processing system. Components must coordinate implementation with Defense Logistics Management Standards prior to use.
4. Subsequent to September 30, 2012, DLMS users must employ the International Organization for Standardization (ISO) Country Codes when providing geographic location by country. The authoritative source for ISO Country Codes is the Global Informational Grid (GIG) Technical Profile (GTP). The existing DLA Transaction Service country code mediation table which will be updated from the authoritative source when it becomes available.
5. This revision to the DLMS Supplement (DS) incorporates Proposed DLMS Changes (PDCs) and Approved DLMS Changes (ADCs) listed. PDCs and ADCs are available from the Defense Logistics Management Standards website: <http://www.dla.mil/j-6/dlms/elibrary/Changes/processchanges.asp>
 - ADC 309, NOA and NOA Reply Transaction Data Content/Mapping including Addition of Type Pack Code for 463L Pallets
 - ADC 436, Administrative Revisions to DLMS Supplements to Remove Obsolete Routing Identifier Code (RIC) "Streamline" Notes and Update MILSTRIP/DLMS Documentation Associated with Routing Identifiers
 - ADC 448, Implementation of International Organization for Standardization (ISO) 3166-1 Codes for the Identification of Countries and their Subdivisions

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
10	ST	Transaction Set Header	M	1			Must use
20	BSR	Beginning Segment for Order Status Report	M	1			Must use

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
* 42	TD3	Carrier Details (Equipment)	O	1			Not Used
* 43	TD4	Carrier Details (Special Handling, or Hazardous Materials, or Both)	O	1			Not Used
* 44	TD5	Carrier Details (Routing Sequence/Transit Time)	O	1			Not Used
* 45	DTM	Date/Time Reference	O	10			Not Used
* LOOP ID - REF					≥1		
* 46	REF	Reference Identification	O	1			Not Used
* 47	DTM	Date/Time Reference	O	>1			Not Used
LOOP ID - N1					200		
50	N1	Name	O	1			Must use
* 60	N2	Additional Name Information	O	2			Not Used
* 70	N3	Address Information	O	2			Not Used
* 80	N4	Geographic Location	O	1			Not Used
* 90	REF	Reference Identification	O	12			Not Used
* 100	PER	Administrative Communications Contact	O	3			Not Used
* 105	PWK	Paperwork	O	1			Not Used
* LOOP ID - LM					10		
* 120	LM	Code Source Information	O	1			Not Used
130	LQ	Industry Code	M	100			Must use

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - HL					1000		
10	HL	Hierarchical Level	M	1			Must use
* 20	PRF	Purchase Order Reference	O	1			Not Used
* LOOP ID - ISR					104		
* 30	ISR	Item Status Report	O	1			Not Used
* 40	PID	Product/Item Description	O	6			Not Used
* 50	QTY	Quantity	O	4			Not Used
* 70	PER	Administrative Communications Contact	O	3			Not Used
80	DTM	Date/Time Reference	O	10			Used
* 86	CS	Contract Summary	O	3		N2/86	Not Used
LOOP ID - REF					≥1		
87	REF	Reference Identification	O	1			Must use
* 88	DTM	Date/Time Reference	O	>1			Not Used
LOOP ID - N1					200		
90	N1	Name	O	1			Must use
* 100	N2	Additional Name Information	O	2			Not Used
* 110	N3	Address Information	O	2			Not Used
* 120	N4	Geographic Location	O	1			Not Used
* 130	REF	Reference Identification	O	12			Not Used
* 140	PER	Administrative Communications Contact	O	3			Not Used
LOOP ID - LM					10		
144	LM	Code Source Information	O	1			Used
145	LQ	Industry Code	M	100			Must use
* LOOP ID - PO1					1000		
* 150	PO1	Baseline Item Data	O	1			Not Used
* 155	CUR	Currency	O	1			Not Used

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
* 160	SLN	Subline Item Detail	O	100			Not Used
* 170	PO3	Additional Item Detail	O	1			Not Used
* 180	PID	Product/Item Description	O	1000			Not Used
* 190	MEA	Measurements	O	40			Not Used
* 200	PKG	Marking, Packaging, Loading	O	25			Not Used
* LOOP ID - ISR					<u>104</u>		
* 210	ISR	Item Status Report	O	1			Not Used
* 220	PID	Product/Item Description	O	6			Not Used
* 230	QTY	Quantity	O	4			Not Used
* 240	DTM	Date/Time Reference	O	10			Not Used
* 250	N1	Name	O	1			Not Used
* 251	N2	Additional Name Information	O	2			Not Used
* 252	N3	Address Information	O	2			Not Used
* 253	N4	Geographic Location	O	1			Not Used
* 260	TD1	Carrier Details (Quantity and Weight)	O	1			Not Used
* 270	TD5	Carrier Details (Routing Sequence/Transit Time)	O	1			Not Used
* 280	TD3	Carrier Details (Equipment)	O	1			Not Used
* 290	TD4	Carrier Details (Special Handling, or Hazardous Materials, or Both)	O	1			Not Used
* 300	REF	Reference Identification	O	12			Not Used
* 310	SAC	Service, Promotion, Allowance, or Charge Information	O	25			Not Used
* LOOP ID - LM					<u>10</u>		
* 320	LM	Code Source Information	O	1			Not Used
330	LQ	Industry Code	M	100			Must use
* LOOP ID - LX					<u>≥1</u>	<u>N2/340L</u>	
* 340	LX	Assigned Number	O	1		N2/340	Not Used
* 350	REF	Reference Identification	O	>1			Not Used
* 360	N1	Name	O	1			Not Used
* 370	DTM	Date/Time Reference	O	10			Not Used
* LOOP ID - LM					<u>10</u>		
* 380	LM	Code Source Information	O	1			Not Used
390	LQ	Industry Code	M	100			Must use

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
* 10	CTT	Transaction Totals	O	1		N3/10	Not Used
20	SE	Transaction Set Trailer	M	1			Must use

Notes:

2/86 Use is limited to intra-organizational transactions.

2/340L The LX loop conveys serial number, lot number, and inventory data.

2/340 The LX loop conveys serial number, lot number, and inventory data.

3/10 The number of line items (CTT01) is the accumulation of the number of HL segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.

ST Transaction Set Header

Pos: 10	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the start of a transaction set and to assign a control number

Semantics:

- The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>	<u>Rep</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use	1
		Description: Code uniquely identifying a Transaction Set					
		Code Name					
		870 Order Status Report					
ST02	329	Transaction Set Control Number	M	AN	4/9	Must use	1
		Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set					
		Federal Note: <i>A unique number assigned by the originator of the transaction set, or the originator's application program.</i>					

BSR Beginning Segment for Order Status Report

Pos: 20	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 6

User Option (Usage): Must use

Purpose: To indicate the beginning of an Order Status Report Transaction Set

Semantics:

1. BSR03 indicates a status report document number assigned by the sender.
2. BSR04 indicates the date of this report from the sender.
3. BSR07 indicates the time of this report from the sender.
4. BSR08 indicates a status report document number assigned by the inquirer.
5. BSR09 indicates the date this report was requested from the sender by the inquirer.
6. BSR10 indicates the time this report was requested from the sender by the inquirer.

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>	<u>Rep</u>
BSR01	850	Status Report Code	M	ID	1/2	Must use	1
		Description: Code indicating the reason for sending the report					
		Code Name					
		8 Response to Notice of Availability					
BSR02	847	Order/Item Code	M	ID	1/2	Must use	1
		Description: Code identifying a group of orders and items					
		Code Name					
		CO All Orders - Unshipped Items					
		DLMS Note:					
		<i>Use to indicate that all orders remain open.</i>					
BSR03	127	Reference Identification	M	AN	1/30	Must use	1
		Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier					
		Federal Note: Use Code "Z" for this data element to satisfy mandatory X12 syntax requirements.					
BSR04	373	Date	M	DT	8/8	Must use	1
		Description: Date expressed as CCYYMMDD					
		Federal Note: This date is the date of the transaction set preparation and corresponds to the Universal Time Coordinate (UTC).					
BSR07	337	Time	O	TM	4/8	Must use	1
		Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)					

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>	<u>Rep</u>
		<p>Federal Note: 1. Express the originating activity's time of transaction set preparation in UTC.</p> <p>2. Express time in a four-position (HHMM) format.</p>					
BSR11	353	Transaction Set Purpose Code	O	ID	2/2	Must use	1
		<p>Description: Code identifying purpose of transaction set</p> <p>Code Name</p> <p>00 Original</p> <p>77 Simulation Exercise</p>					
		<p>DLMS Note:</p> <p><i>Use to identify a simulated mobilization exercise transaction set. Activities initiating simulated mobilization exercises must ensure complete coordination with all activities involved. All transaction set recipients must use extreme caution to ensure that individual transactions do not process as action documents which affect accountable records.</i></p>					

N1 Name

Pos: 50	Max: 1
Heading - Optional	
Loop: N1	Elements: 5

User Option (Usage): Must use**Purpose:** To identify a party by type of organization, name, and code**Syntax Rules:**

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

Federal Note:

Must use this 1/N1/050 loop to identify the organization originating the transaction set.

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>	<u>Rep</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use	1

Description: Code identifying an organizational entity, a physical location, property or an individual

Federal Note: *Use any code.*

DLMS Note: *1. Use only one of code 98 or CY.*

2. For DLMS use, only the following codes are authorized.

3. For conversion between MILS and DLMS formats, the transaction originator will always be identified by Qualifier CY using the MILSTRIP Country Code.

4. Identification of the Freight Forwarder (FF) or Country Representative (CR) are identified as DLMS enhancement; see introductory DLMS note 3a. Use of this enhancement requires a second iteration of the N1 loop (refer to ADC 309).

Code Name

98 Freight Management Facilitator

DLMS Note:

This is a DLMS enhancement to identify the FF originating the transaction set.

CY Country

DLMS Note:

1. Use to identify the FMS country associated with the NOA reply.

2. Use as a DLMS enhancement to identify the CR originating the transaction set.

N102	93	Name	X	AN	1/60	Used	1
------	----	-------------	---	----	------	------	---

Description: Free-form name

DLMS Note: *This is a DLMS enhancement for identification of the FF or CR by clear text where coded address is not available.*

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>	<u>Rep</u>
N103	66	Identification Code Qualifier	X	ID	1/2	Must use	1

Description: Code designating the system/method of code structure used for Identification Code (67)

Code Name

38 Country Code

DLMS Note:

Use with N101 Qualifier CY to identify the FMS country code (MILSTRIP) applicable to the NOA reply. (Must be consistent with the NOA and original requisition content). Use to identify the Security Cooperation Customer Code (previously known as the MILSTRIP Country and Activity Code). Refer to ADC 448

A2 Military Assistance Program Address Code (MAPAC)

DLMS Note:

This is a DLMS enhancement for use of the constructed MAPAC to identify the FF or CR. Requires coordination prior to use.

N104	67	Identification Code	X	AN	2/80	Must use	1
------	----	----------------------------	---	----	------	----------	---

Description: Code identifying a party or other code

N106	98	Entity Identifier Code	O	ID	2/3	Must use	1
------	----	-------------------------------	---	----	-----	----------	---

Description: Code identifying an organizational entity, a physical location, property or an individual

Code Name

FR Message From

Federal Note:

Must use with the appropriate 1/N101/050 code to indicate that the organization cited in N104 is originating the transaction set.

HL Hierarchical Level

Pos: 10	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Comments:

1. The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
2. The HL segment defines a top-down/left-right ordered structure.
3. HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
4. HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
5. HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
6. HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

DLMS Note:

The transaction set hierarchical data structure is shipment unit only as identified by the FMS notice number assigned to control the shipment.

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>	<u>Rep</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use	1
		<p>Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure</p> <p>Federal Note: <i>In the first 2/HL/010 loop iteration, cite numeric 1. In each subsequent loop iteration, increase incrementally by 1.</i></p>					
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use	1
		<p>Description: Code defining the characteristic of a level in a hierarchical structure</p> <p>Code Name</p> <p>S Shipment</p> <p>DLMS Note:</p> <p><i>Use to identify the individual shipment loops addressed in the FMS NOA reply.</i></p>					

DTM Date/Time Reference

Pos: 80	Max: 10
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Used**Purpose:** To specify pertinent dates and times**Syntax Rules:**

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>	<u>Rep</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use	1

Description: Code specifying type of date or time, or both date and time

Federal Note: Use to identify the originator's date of transaction preparation and other dates associated with the transaction.

Code Name

097 Transaction Creation

DLMS Note:

Use to indicate the date of transaction preparation.

108 Postmark

DLMS Note:

Use to identify the date release and shipping instructions were mailed. Use only when mailing separate release and shipping instructions.

DTM02	373	Date	X	DT	8/8	Must use	1
-------	-----	------	---	----	-----	----------	---

Description: Date expressed as CCYYMMDD

REF Reference Identification

Pos: 87	Max: 1
Detail - Optional	
Loop: REF	Elements: 2

User Option (Usage): Must use

Purpose: To specify identifying information

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>	<u>Rep</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use	1
		<p>Description: Code qualifying the Reference Identification</p> <p>Federal Note: Use any code.</p> <p>DLMS Note: For DLMS use, only the following codes are authorized.</p> <p>Code Name</p> <p>FN Forwarder's/Agent's Reference Number</p> <p>DLMS Note: Use to identify the customer (CR/FF) assigned transportation order number used for internal control of the shipment.</p> <p>K1 Foreign Military Sales Notice Number</p> <p>DLMS Note: Must use to identify the FMS NOA number assigned to the shipment.</p> <p>LO Load Planning Number</p> <p>DLMS Note: Use to identify the number of transactions included in the shipment.</p>					
REF02	127	Reference Identification	X	AN	1/30	Must use	1
		<p>Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier</p>					

N1 Name

Pos: 90	Max: 1
Detail - Optional	
Loop: N1	Elements: 4

User Option (Usage): Must use**Purpose:** To identify a party by type of organization, name, and code**Syntax Rules:**

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

Federal Note:

Must use this 2/N1/090 loop to identify the organization to receive the transaction.

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>	<u>Rep</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use	1
Description: Code identifying an organizational entity, a physical location, property or an individual							
Federal Note: <i>Use any code.</i>							
DLMS Note: <i>For DLMS use, only the following codes are authorized.</i>							
Code Name							
CI		Consignor					
DLMS Note:							
<i>Use to indicate the shipping activity (activity initiating the NOA).</i>							
ST		Ship To					
DLMS Note:							
<i>Use to identify the ship to address when the ship to instructions are different than those provided originally.</i>							
N103	66	Identification Code Qualifier	X	ID	1/2	Must use	1
Description: Code designating the system/method of code structure used for Identification Code (67)							
Code Name							
1		D-U-N-S Number, Dun & Bradstreet					
9		D-U-N-S+4, D-U-N-S Number with Four Character Suffix					
10		Department of Defense Activity Address Code (DODAAC)					
M4		Department of Defense Routing Identifier Code (RIC)					
N104	67	Identification Code	X	AN	2/80	Must use	1
Description: Code identifying a party or other code							
N106	98	Entity Identifier Code	O	ID	2/3	Used	1
Description: Code identifying an organizational entity, a physical location, property or an individual							

Code Name

TO Message To

Federal Note:

Must use with N101 code CI to indicate that the organization cited in N104 is receiving the transaction set.

LM Code Source Information

Pos: 144	Max: 1
Detail - Optional	
Loop: LM	Elements: 1

User Option (Usage): Used

Purpose: To transmit standard code list identification information

Comments:

1. LM02 identifies the applicable industry code list source information.

Federal Note:

Use this 2/LM/144 loop to identify coded information maintained in department or agency documentation.

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>	<u>Rep</u>
LM01	559	Agency Qualifier Code	M	ID	2/2	Must use	1

Description: Code identifying the agency assigning the code values

Code Name

DF Department of Defense (DoD)

LQ Industry Code

Pos: 145	Max: 100
Detail - Mandatory	
Loop: LM	Elements: 2

User Option (Usage): Must use**Purpose:** Code to transmit standard industry codes**Syntax Rules:**

1. C0102 - If LQ01 is present, then LQ02 is required.

Federal Note:

Use to identify codes consistent with management information requirements.

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>	<u>Rep</u>
LQ01	1270	Code List Qualifier Code	O	ID	1/3	Must use	1

Description: Code identifying a specific industry code list

Federal Note: *Use any code.*

DLMS Note: *For DLMS use, only the following codes are authorized.*

Code Name

0 Document Identification Code

79 Priority Designator Code

DLMS Note:

Recommend using in all requisitions

96 Shipment Release Code

DLMS Note:

Use to provide FMS NOA shipment release instructions.

A9 Supplemental Data

DLMS Note:

1. Use to identify supplemental address/data.

2. Future streamlined data; see introductory DLMS note 3c.

AJ Utilization Code

DLMS Note:

1. Under DLSS, this is the first position of the document serial number.

2. DLMS enhancement; see introductory DLMS note 3a.

AL Special Requirements Code

Federal Note:

Use to identify the precedence, special handling, and processing requirements.

DLMS Note:

1. Under DLSS, this is carried in the required delivery date field.

2. DLMS enhancement; see introductory DLMS note 3a.

COG Cognizance Symbol

DLMS Note:

Use to identify the material cognizance symbol (COG) of the end item. Indicate NSL for non-stock numbered listed items. This is a Navy-unique data element meaningful to Navy only; Non-Navy Components are to perpetuate without action.

IMC Item Management Code

DLMS Note:

Use to identify the Item Management Code (IMC) for integrated material management. This is a Navy-unique data element meaningful to Navy only; Non-Navy Components are to perpetuate without action.

Code Name

MCC Material Control Code

DLMS Note:

Use to identify the Material Control Code (MCC) for special inventory reporting. This is a Navy-unique data element meaningful to Navy only; Non-Navy Components are to perpetuate without action.

SMI Special Material Identification Code

DLMS Note:

Use to identify the Special Material Identification Code (SMIC) for an end item. This is a Navy-unique data element meaningful to Navy only; Non-Navy Components are to perpetuate without action.

LQ02	1271	Industry Code	X	AN	1/30	Must use	1
------	------	----------------------	---	----	------	----------	---

Description: Code indicating a code from a specific industry code list

SE Transaction Set Trailer

Pos: 20	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Comments:

- SE is the last segment of each transaction set.

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>	<u>Rep</u>
SE01	96	Number of Included Segments	M	N0	1/10	Must use	1
		Description: Total number of segments included in a transaction set including ST and SE segments					
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use	1
		Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set					
		Federal Note: <i>Cite the same number as the one cited in ST02.</i>					